

TG1260 & TG2460 SERIES TICKET AND RECEIPT PRINTERS



A RELIABLE RANGE OF 60MM TICKET AND RECEIPT PRINTERS

The TG range of ticket and receipt printers are suitable for various applications. They can be used in self-service kiosks, ATMs, gaming machines, parking meters, vending machines and much more.

These printers provide crisp and high resolution print quality of up to 200 DPI on 60mm paper. Paper thickness is rated from 60 to 80 µm and print speeds are up to 140 mm/sec.

Barcodes and multiple character sets are supported by the TG series. UPC-A, UPC-E, EAN13, EAN8, CODE39, CODE93, CODE128, CODE32, ITF, CODABAR and QRCODE barcode standards are supported. As well as these, European, International, Nordic, Portuguese, Thai, Arabic, Chinese and Russian character sets can be printed.

The TG series is also extremely reliable. An example of this being the cutter rated at over 1,000,000 cuts. A myriad of sensors also keep the printer running smoothly and safely.

APPLICATIONS


- Self-service kiosks
- Gaming machines
- ATMs
- Vending machines

KEY FEATURES




Fast print speeds

Print speeds of 140 mm/sec mean minimal wait times for users.



Multiple interfaces

RS232 and USB interfaces ensure that connectivity is always achievable.



Barcodes

UPC-A & E, EAN13 & 8, CODE39, 93, 128, 32, ITF, CODABAR and QRCODE are supported.



Various character sets

European, International, Thai, Nordic, Portuguese, Arabic, Chinese and Russian character sets are supported.

| Model | TG2460H Tear Off | TG2460H Cutter | TG1260H Cutter |
|------------------------------|---|---|---|
| Printing Method | Thermal with fixed head | Thermal with fixed head | Thermal with fixed head |
| Number of Dots | 8 dots/mm | 8 dots/mm | 8 dots/mm |
| Columns | 32 - 42 - 56 | 32 - 42 - 56 | 32 - 42 - 56 |
| Print Resolution | 203 DPI | 203 DPI | 203 DPI |
| Print Speed | 140 mm/sec | 140 mm/sec | 60 mm/sec |
| Character Sets | PC437, PC850, PC860, PC863, PC865, PC858, PC866, GB2312 | PC437, PC850, PC860, PC863, PC865, PC858, PC866, GB2312 | PC437, PC850, PC860, PC863, PC865, PC858, PC866, GB2312 |
| Printing Format | Normal height and width from 1 to 4, bold, negative, underlined, script, italic | Normal height and width from 1 to 4, bold, negative, underlined, script, italic | Normal height and width from 1 to 4, bold, negative, underlined, script, italic |
| Barcodes | UPC-A, UPC-E, EAN13, EAN8, ITF, CODABAR, CODE39, CODE93, CODE128, CODE32, QRCODE | UPC-A, UPC-E, EAN13, EAN8, ITF, CODABAR, CODE39, CODE93, CODE128, CODE32, QRCODE | QRCODE |
| Printing Direction | Straight, 180° | Straight, 180° | Straight, 180° |
| Paper Width | 60 mm | 60 mm | 60 mm |
| Paper Weight | 55 to 77 g/m ² | 55 to 77 g/m ² | 55 to 77 g/m ² |
| Paper Thickness | 60 to 80 µm | 60 to 80 µm | 60 to 80 µm |
| Roll Dimension | Maximum 100 mm | Maximum 100 mm | Maximum 120 mm |
| Sensors | Head temperature, Paper jamming, Paper presence, Notch presence, Paper end (optional) | Head temperature, Paper jamming, Paper presence, Notch presence, Paper end (optional) | Head temperature, Paper jamming, Paper presence, Notch presence, Paper end (optional) |
| Emulation | Escape Command compatibility | Escape Command compatibility | Escape Command compatibility |
| Interfaces | RS232 USB | RS232 USB | RS232 USB |
| Data Buffer | 2 kB | 2 kB | 2 kB |
| Flash Memory | 1 MB | 1 MB | 4 MB |
| Graphic Memory | 2 logos of 448 x 584 dots | 2 logos of 448 x 584 dots | 2 logos of 448 x 584 dots |
| Drivers | Windows XP, Vista, 7, 8, 8.1, 10, CE 3.0/5.0 Linux 32 / 64 bit | Windows XP, Vista, 7, 8, 8.1, 10, CE 3.0/5.0 Linux 32 / 64 bit | Windows XP, Vista, 7, 8, 8.1, 10, CE 3.0/5.0 Linux 32 / 64 bit |
| Software Tools | FontMake, LogoMake, UpgCePrn, Status Monitor | FontMake, LogoMake, Upg-CePrn, Status Monitor | Status Monitor |
| Power Supply | 24V +/- 10% | 24V +/- 10% | 12V +/- 10% |
| Power Consumption | 0.62 A typical | 0.62 A typical | 0.66 A typical |
| MTBF | 420,000 hours | 420,000 hours | 420,000 hours |
| Head Life | 50 Km / 100M Pulses | 50 Km / 100M Pulses | 50 Km / 100M Pulses |
| Operating Temperature | -20 ~ 70°C | -20 ~ 70°C | -20 ~ 70°C |
| Dimensions | 100 x 93 x 120 mm (L x W x H) | 118 x 114 x 80 mm (L x W x H) | 118 x 114 x 80 mm (L x W x H) |
| Weight | 600 g | 600 g | 600 g |
| Paper Roll Position | 180° arc behind printer | 180° arc behind printer | 180° arc behind printer |

JEA reserves the right to change or update, without notice, any information contained herein.